

Twist-Lock Electronic Photocontrol LongLife II

Exclusive Features



Zero Cross Switching Technology: protects the device from inrush currents, commonly found in LED Luminaires.



Intelligent Microprocessor: assures advanced Performance & Reliability

Self-Healing Relay

SELF-Healing Relay: allows unattended field restoration. Stuck relay contacts are a common failure point. Our Patent Pending technology actually works to un-stick the contacts, thus preventing wasted energy (day burners) and service calls. Tested at more than **325 years with a 1000 Watt Tungsten Lamp**



3 Tier Power Supply Circuitry: 640 Joule 33 mm MOV rated @ 40,000 Amps for primary protection Dual Zener Diode for secondary protection. 3rd Layer of protection using a precision voltage regulator.



Tru-Filter®: spectral sensitivity matches that of the Human Eye; while competitor's Silicon Photodetector comes nowhere close.

Phone: (803) 939-4700
Fax: (803) 939-4777
Email: info@RipleyLightingControls.com

www.RipleyLightingControls.com



Ripley's exclusive

LongLife II Photocontrol

"NEW Generation of Technologies that change the Game"

Ripley Lighting Controls is pioneering new technologies raising the bar in the Street and Area Lighting Industry.

	6390LL-BK	6394LL	6395LL
Nominal Voltage 60 Hz	120/208/240/277	480	347
Voltage Range	105—305	432—528	312—382
Fail Mode	On		
Load Rating	1000 Watt Tungsten / 1800 VA Ballast		
Operating Temperature	-40C to +70C (-40F to +158F)		
Photocell	Infrared Filtering Silicon Phototransistor		
Dielectric Strength	5000 Volts between current carrying parts and metal surfaces		
Surge Protection	Primary: 640 Joule MOV rated at 40,000 amp surge current—protects not only the photocontrol, but also the LED fixture Secondary: 2 Zener diodes Third: Voltage Regulator		
Power Consumption	0.5 watts @ 120 V		
Time Delay Off (Instant On)	3 to 5 seconds		
Operating Light Levels (Standard Settings)	Turn On 1.5 FC ± .25 / Turn Off by 2.25 FC (Off:On Ratio = 1.5:1)		
ANSI Color Coded Cover: double-wall thickness, UV Stabilized Permanent Color LongLife polymer with extra UV inhibitor	Black	Yellow	Green
Options			
Fail Off	-FO (Green)	N/A	N/A
Freguency	60Hz		
Applicable with			

Other Exclusive Features:

- Electrolytic Capacitors rated 105 °C, with minimum 20,000 hour life at maximum voltage, current, & temperature
- Completed circuit boards are conformal coated with silicone for Long Life
- Double-wall thickness for strength and longevity in constant outdoor environment, optimized black Long Life polymer with maximum UV inhibitor
- 1:1 Ratio Capable saves energy by reducing burn time. Allows for the light to turn off at the same light level as the turn on value.
- RoHS Compliant & packaged in Biodegradable Bags



Meets or exceeds rigid quality requirements of applicable ANSI C136.10, and C136.24 and C136.41

© 2021 by Ripley Lighting Controls, a Unit of Electros witch. All rights reserved. The information in this document is provided for informational use only and is subject to change without notice.