

# Wire-In PhotoControl Pencil Control



Swivel-base design with thumb-screw lock down for precise positioning

## Typical Applications

- Security Systems
- Low Voltage Lighting
- Landscaping

## Exclusive Features

- High Impact Thermoplastic Base
- Swivel-base Design
- Thumb-screw lock down

Meets or exceeds rigid quality requirements of applicable ANSI C136.10 and C136.24 Standards

	<b>7051-48VDC</b>	<b>7051-120V</b>
Nominal Voltage	48 (DC)	120 (AC) 60 Hz
Voltage Range	44–52 (DC) (+/- 10% of rated voltage)	105–135
Fail Mode	On (contacts normally closed)	
Load Rating	1000 Watt Tungsten / 1200 VA Ballast	
Operating Temperature	-40C to +70C (-40F to +158F)	
Photocell	Chemically Coated Cadmium Sulfide	
Dielectric Strength	5000 Volts between current carrying parts and metal surfaces	
Time Delay	up to 2 minutes	
Operating Light Levels	Turn On 2 FC ±1 / Turn Off by 10 FC	
ANSI Color Coded Cover	Black	

For 1/2" NPT Conduit Knock-out Mounting  
1/2" Conduit Lock-ring Included  
3 #18 AWG Leads



Wiring

Phone: (803) 939-4700  
Fax: (803) 939-4777  
Email: [info@RipleyLightingControls.com](mailto:info@RipleyLightingControls.com)

[www.RipleyLightingControls.com](http://www.RipleyLightingControls.com)

© 2021 by Ripley Lighting Controls, a Unit of Electroswitch. All rights reserved. The information in this document is provided for informational use only and is subject to change without notice.